

ROUND CO-AXIAL METAL CEILING Loudspeakers



- > **RCS5/TCOAX**
- > **RCS5/FTSCOAX**

TECHNICAL SPECIFICATIONS

Rated power, Watts	10
Tappings 100 volt line, Watts	10/5/2.5/1.25
Transformer Impedance, Ohms, 100V	1k/2k/4k/8k
Tappings 70.7 volt line, Watts	5/2.5/1.25/0.625
Driver impedance, Ohms	8
Effective frequency range, Hz (BSEN60268-5)	RCS5/TCOAX: 70-18.5KHz RCS5/FTSCOAX: 130-18.5KHz
S.P.L. @ 1m, 1 watt, dB, Test Signal Bandwidth 100 Hz-10 kHz	RCS5/TCOAX: 91 RCS5/FTSCOAX: 91
S.P.L. @ Full power Octave Bandwidth, dB	RCS5/TCOAX: 101 RCS5/FTSCOAX: 101
Acoustic Power (dB-PWL@1 watt) 1 k/2kHz, dB	RCS5/TCOAX: 88/88 RCS5/FTSCOAX: 88/86
Dispersion at 1k/2kHz, Degrees	RCS5/TCOAX: 180/180 RCS5/FTSCOAX: 180/160
Directivity Axial Q factor, 1k/2kHz	RCS5/TCOAX: 2.1/4.0 RCS5/FTSCOAX: 2.0/5.3
Dimensions, diameter, mm	Ø189
Net weight, Kgs	RCS5/TCOAX: 1.2 RCS5/FTSCOAX: 1.5
Colour/Finish	White RAL9016
Material	Steel
Mounting	Torsion springs
Cut-out, mm	RCS5/TCOAX: Ø160 RCS5/FTSCOAX: Ø164


- > RCS5/FTSCOAX is BS5839 Part 8 voice alarm compliant

EASE, CATT, ULYSSES and Architectural specifications are supplied on the disc inserted at the back of this folder
 Manufacturer reserves the right to alter specifications without notice – March 2007


RCS5/TCOAX RCS5/FTSCOAX

ROUND CO-AXIAL METAL CEILING LOUDSPEAKERS


▼ **RCS5/TCOAX**
side view
unit: **mm**




▼ **RCS5/FTSCOAX**
side view
(gland not supplied)
unit: **mm**



▼ **circuit diagram**
RCS5/FTSCOAX



speech octave band sensitivity



Effective Frequency Range

- **RCS5/TCOAX** 70Hz - 18.5kHz
- **RCS5/FTSCOAX** 130Hz - 18.5kHz



Penton UK Ltd
Unit 2 Teville Industrials | Dominion Way | Worthing | West Sussex | BN14 8NW
T: +44 (0)1903 215315 | F: +44(0)1903 215415 | E: SALES@PENTONUK.CO.UK
www.penton.org